




EZIO

EZIO® 4 pt. 24VDC In/ 4 pt. 110VAC Out Module

EZIO-4DCI4ACO Snap-in



EZIO-4DCI4ACO
\$34

EZIO-4DCOP4ACO
\$44

EZIO-4DCI4ACO
Screw-down

Model Specifications		
AC/DC Power Supply Specs	Voltage Range	
DC Output Specs	Number of Inputs	4 (sink/source)
	Input Voltage Range	10-28 VDC
	Peak Voltage	40 VDC
	Input Current	1.92 mA @ 12 VDC 4.0 mA @ 24 VDC
	Maximum Input Current	5 mA @ 28 VDC
	Input Impedance	5.6k @ 10-28 VDC
	ON Voltage Level	> 10 VDC
	OFF Voltage Level	< 2 VDC
	Min. ON Current	1.5 mA
	Min. OFF Current	0.2 MmA
	OFF to ON Response	2-4 ms, typical 3 ms
	ON to OFF Response	2-4 ms, typical 3 ms
	Status Indicators	Red LED for each output
	Commons	1 point
	Fuse	No fuse
	Base Power Required (3.3V)	Typical 7.5 mA (all inputs on)
	Optical Isolation	2500 Volt
Wires	1 of 14 AWG, 2 of 18 AWG, 4 of 22 AWG	
AC Output Specs	Number of Output Points	4
	Number of Commons	1
	Output Voltage Range	20-132 VAC
	Peak Voltage	180 Volt
	ON Voltage Drop	1.2 V @ 1A
	Maximum Current	1.2 A @ 25°C, 0.8A @ 50°C for each output
	Maximum Leakage Current	1mA @ 132 VAC
	Maximum Inrush Current	38Amps for 16.6ms
	Minimum Load	15mA
	OFF to ON Response	max 1/2 cycle
	ON to OFF Response	max 1/2 cycle
	Fuse	No fuse
	Base Power Required (3.3V)	35mA for all 4 on
	Optical Isolation	2500 Volt
	Wires	1 of 14 AWG, 2 of 18 AWG, 4 of 22 AWG

Pinout Information	
Pin No.	EZIO-4DCI4ACO
1	AC Input(1)
2	AC Input(2)
3	AC Input(3)
4	AC Input(4)
5	GND
6	DC Output(1)
7	DC Output(2)
8	DC Output(3)
9	DC Output(4)
10	AC_Common
11	Not Connected

Terminal Block
300 Volt/10 Amp/
14AWG UL Rating

Delivery Code STK

